


DIN 6796


锥型垫圈

Comcal Spring Washer

材料: 弹簧钢 65 Mn
Material: 65Mn



| 规格 | 2 | 2.5 | 3 | 3.5 | 4 | 5 | 6 | 7 | 8 | 10 |
|-------|-----|------|------|------|------|------|-----|------|------|------|
| d1 | 2.2 | 2.7 | 3.2 | 3.7 | 4.3 | 5.3 | 6.4 | 7.4 | 8.4 | 10.5 |
| d2 | 5 | 6 | 7 | 8 | 9 | 11 | 14 | 17 | 18 | 23 |
| s | 0.4 | 0.5 | 0.6 | 0.8 | 1 | 1.2 | 1.5 | 1.75 | 2 | 2.5 |
| h max | 0.6 | 0.72 | 0.85 | 1.06 | 1.3 | 1.55 | 2 | 2.3 | 2.6 | 3.2 |
| h min | 0.5 | 0.61 | 0.72 | 0.92 | 1.12 | 1.35 | 1.7 | 2 | 2.24 | 2.8 |



| 规格 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 27 | 30 |
|-------|------|------|------|------|-----|------|------|------|-----|
| d1 | 13 | 15 | 17 | 19 | 21 | 23 | 25 | 28 | 31 |
| d2 | 29 | 35 | 39 | 42 | 45 | 49 | 56 | 60 | 70 |
| s | 3 | 3.5 | 4 | 4.5 | 5 | 5.5 | 6 | 6.5 | 7 |
| h max | 3.95 | 4.65 | 5.25 | 5.8 | 6.4 | 7.05 | 7.75 | 8.35 | 9.2 |
| h min | 3.43 | 4.04 | 4.58 | 5.08 | 5.6 | 6.15 | 6.77 | 7.3 | 8 |